

PACi NX Series Elite adaptive ducted unit - PF3 - R32

Adaptive ducted unit - PF3.

2 installation possibilities (horizontal / vertical) with high ESP 150Pa allows flexible installation.



			Single phase													
			3,6 kW		5,0 kW		6,0 kW		7,1 kW		10,0 kW		12,5 kW		14,0 kW	
Kit			KIT-36PF3ZH5		KIT-50PF3ZH5		KIT-60PF3ZH5		KIT-71PF3ZH5		KIT-100PF3ZH5		KIT-125PF3ZH5		KIT-140PF3ZH5	
Remote controller			CZ-RTC5B		CZ-RTC5B		CZ-RTC5B		CZ-RTC5B		CZ-RTC5B		CZ-RTC5B		CZ-RTC5B	
Cooling capacity	Nominal (Min - Max)	kW	3,6(1,2-4,0)		5,0(1,2-5,6)		5,7(1,2-6,3)		6,8(2,2-7,8)		9,5(3,1-11,4)		12,1(3,2-13,6)		13,4(3,3-15,3)	
EER ¹⁾	Nominal (Min - Max)	W/W	4,24(3,57-5,45)		3,42(3,11-5,45)		3,68(3,15-5,45)		3,74(2,41-5,64)		4,09(2,82-5,08)		3,53(3,00-5,00)		3,38(2,59-4,18)	
SEER / η _{sc} ²⁾			6,8 A++		6,1 A++		7,1 A++		7,1 A++		7,4 A++		281,7%		275,9%	
Pdesign		kW	3,6		5,0		5,7		6,8		9,5		12,1		13,4	
Input power	Nominal (Min - Max)	kW	0,85(0,22-1,12)		1,46(0,22-1,80)		1,55(0,22-2,00)		1,82(0,39-3,24)		3,23(0,61-4,04)		3,43(0,64-4,54)		3,96(0,79-5,90)	
Annual energy consumption ³⁾		kWh/a	185		287		281		332		447		—		—	
Heating capacity	Nominal (Min - Max)	kW	4,0(1,2-5,0)		5,6(1,2-6,5)		7,0(1,2-8,0)		7,5(2,0-9,0)		10,8(3,1-13,5)		13,5(3,2-15,4)		15,5(3,3-17,4)	
COP ¹⁾	Nominal (Min - Max)	W/W	4,17(3,23-5,45)		3,61(2,97-5,45)		3,74(3,33-5,45)		4,03(3,16-5,41)		3,88(3,07-5,25)		3,46(3,06-5,16)		3,33(3,14-4,29)	
SCOP / η _{sh} ²⁾			4,5 A+		4,2 A+		4,4 A+		4,7 A++		4,3 A+		165,0%		162,6%	
Pdesign at -10 °C		kW	3,6		4,2		4,7		4,7		7,8		9,3		9,5	
Input power	Nominal (Min - Max)	kW	0,96(0,22-1,55)		1,55(0,22-2,19)		1,87(0,22-2,40)		1,86(0,37-2,85)		2,78(0,59-4,40)		3,90(0,62-5,04)		4,65(0,77-5,55)	
Annual energy consumption ³⁾		kWh/a	1120		1333		1495		1393		2540		—		—	
Indoor unit			S-3650PF3E		S-3650PF3E		S-6071PF3E		S-6071PF3E		S-1014PF3E		S-1014PF3E		S-1014PF3E	
External static pressure ⁴⁾	Nominal (Min - Max)	Pa	30(10-150)		30(10-150)		30(10-150)		30(10-150)		40(10-150)		50(10-150)		50(10-150)	
Air flow	Hi / Med / Lo	m ³ /min	14,0/13,0/10,0		16,0/15,0/12,0		21,0/19,0/15,0		21,0/19,0/15,0		20,0/26,0/21,0		34,0/29,0/23,0		36,0/32,0/25,0	
Moisture removal volume		L/h	0,9		1,9		1,7		2,7		3,2		4,1		4,9	
Sound pressure ⁵⁾	Hi / Med / Lo	dB(A)	30/27/22		34/30/25		30/26/23		30/26/23		33/29/25		35/31/27		39/35/29	
Sound power	Hi / Med / Lo	dB(A)	53/50/45		57/53/48		53/49/46		53/49/46		56/52/48		58/54/50		62/58/52	
Dimension	HxWxD	mm	250x800x730		250x800x730		250x1000x730		250x1000x730		250x1400x730		250x1400x730		250x1400x730	
Net weight		kg	25		25		30		30		39		39		39	
nanoe X Generator			Mark 2		Mark 2		Mark 2		Mark 2		Mark 2		Mark 2		Mark 2	
Outdoor unit			U-36PZH3E5		U-50PZH3E5		U-60PZH3E5		U-71PZH4E5		U-100PZH4E5		U-125PZH4E5		U-140PZH4E5	
Power supply		V	220-230-240		220-230-240		220-230-240		220-230-240		220-230-240		220-230-240		220-230-240	
Current	Cool	A	4,20-4,00-3,85		6,90-6,60-6,35		7,25-6,95-6,65		9,20-8,80-8,45		11,50-11,00-10,50		16,80-16,00-15,40		19,40-18,50-17,70	
	Heat	A	4,70-4,50-4,30		7,35-7,00-6,75		8,65-8,30-7,95		9,40-9,00-8,60		13,60-13,10-12,60		19,10-18,20-17,50		22,70-21,70-20,80	
Air flow	Cool / Heat	m ³ /min	34,1/36,4		42,0/42,0		42,0/42,0		62,0/66,0		76,0/70,0		86,0/78,0		89,0/83,0	
Sound pressure	Cool / Heat (Hi)	dB(A)	43/44		46/48		47/50		48/50		52/52		55/55		56/56	
Sound power	Cool / Heat (Hi)	dB(A)	62/64		64/67		65/69		65/67		69/69		73/73		74/74	
Dimension	HxWxD	mm	695x875x320		695x875x320		695x875x320		996x980x370		996x980x370		996x980x370		996x980x370	
Net weight		kg	42		42		43		66		84		86		86	
Piping diameter	Liquid	Inch (mm)	1/4 (6,35)		1/4 (6,35)		1/4 (6,35) ⁶⁾		3/8 (9,52)		3/8 (9,52)		3/8 (9,52)		3/8 (9,52)	
	Gas	Inch (mm)	1/2 (12,70)		1/2 (12,70)		1/2 (12,70) ⁷⁾		5/8 (15,88)		5/8 (15,88)		5/8 (15,88)		5/8 (15,88)	
Pipe length range		m	3~40		3~40		3~40		5~60		5~100		5~100		5~100	
Elevation difference (in / out) ⁸⁾		m	15/30		15/30		15/30		15/30		15/30		15/30		15/30	
Pre-charged pipe length		m	30		30		30		30		30		30		30	
Additional gas amount		g/m	15		15		15		30		40		40		40	
Refrigerant (R32) / CO ₂ Eq.		kg / T	1,13/0,76		1,13/0,76		1,15/0,78		1,95/1,32		2,70/1,82		3,00/2,03		3,00/2,03	
Operating range	Cool Min - Max	°C	-15~+46		-15~+46		-15~+46		-15~+52		-20 ⁹⁾ ~+52		-20 ⁹⁾ ~+52		-20 ⁹⁾ ~+52	
	Heat Min - Max	°C	-20~+24		-20~+24		-20~+24		-20~+24		-20~+24		-20~+24		-20~+24	

Technical focus

- 2 installation possibilities (horizontal / vertical)
- Maximum external static pressure: 150 Pa
- Selectable inlet air position (rear / bottom entry)
- Improved drain pan suitable for both horizontal / vertical installation
- Drain pump included
- nanoe™ X (Generator Mark 2: 9,6 trillion hydroxyl radicals/sec) as standard for the long duct piping case*
- **New** BION air pollutant filter for certain types of pollutants, such as nitrogen dioxide (NO₂), nitrogen oxides (NO_x) and Ozone (O₃) (optional)
- Wired remote control CZ-RTC6WBL and CZ-RTC6BL allows easy system setting via Bluetooth®

* The performance of nanoe™ X air can be expected even by 10 m long duct by Panasonic internal survey.


2 installation possibilities (horizontal / vertical)

Vertical installation is available. ESP 150Pa, sufficient for remotely installing units away from the rooms.



Improved drain pan design

Drain pan is shared in both cases horizontal and vertical installation. No need to modify the unit.





CZ-RTC5B

+ COMPATIBLE WITH ALL PANASONIC CONNECTIVITY SOLUTIONS. FOR DETAILED INFORMATION GO TO THE CONTROL SYSTEMS SECTION

Optional:



CONEX

CONEX wired remote controller, white, CZ-RTC6W/BL/BLW

CONEX

CONEX wired remote controller, black, CZ-RTC6/BL/BLW



Infrared remote controller, CZ-RWS3 + CZ-RWRC3



Econavi sensor, CZ-CENSC1

Three phase

Kit	Three phase				
	7,1 kW	10,0 kW	12,5 kW	14,0 kW	
Remote controller	KIT-71PF3ZH48	KIT-100PF3ZH48	KIT-125PF3ZH48	KIT-140PF3ZH48	
Remote controller	CZ-RTC5B	CZ-RTC5B	CZ-RTC5B	CZ-RTC5B	
Cooling capacity	Nominal (Min - Max) kW	6,8[2,2 - 7,8]	9,5[3,1 - 11,4]	12,1[3,2 - 13,6]	13,4[3,3 - 15,3]
EER ¹⁾	Nominal (Min - Max) W/W	3,74[2,41 - 5,64]	4,09[2,82 - 5,08]	3,53[3,00 - 5,00]	3,38[2,59 - 4,18]
SEER / η _{s,c} ²⁾		7,1 A++	7,4 A++	281,0%	275,2%
Pdesign	kW	6,8	9,5	12,1	13,4
Input power	Nominal (Min - Max) kW	1,82[0,39 - 3,24]	2,32[0,61 - 4,04]	3,43[0,64 - 4,54]	3,96[0,79 - 5,90]
Annual energy consumption ³⁾	kWh/a	332	447	—	—
Heating capacity	Nominal (Min - Max) kW	7,5[2,0 - 9,0]	10,8[3,1 - 13,5]	13,5[3,2 - 15,4]	15,5[3,3 - 17,4]
COP ¹⁾	Nominal (Min - Max) W/W	4,03[3,16 - 5,41]	3,88[3,07 - 5,25]	3,46[3,06 - 5,16]	3,33[3,14 - 4,29]
SCOP / η _{s,h} ²⁾		4,7 A++	4,3 A+	165,0%	162,6%
Pdesign at -10 °C	kW	4,7	7,8	9,3	9,5
Input power	Nominal (Min - Max) kW	1,86[0,37 - 2,85]	2,78[0,59 - 4,40]	3,90[0,62 - 5,04]	4,65[0,77 - 5,55]
Annual energy consumption ³⁾	kWh/a	1394	2540	—	—
Indoor unit		S-6071PF3E	S-1014PF3E	S-1014PF3E	S-1014PF3E
External static pressure ⁴⁾	Nominal (Min - Max) Pa	30[10 - 150]	40[10 - 150]	50[10 - 150]	50[10 - 150]
Air flow	Hi / Med / Lo m ³ /min	21,0/19,0/15,0	32,0/26,0/21,0	34,0/29,0/23,0	36,0/32,0/25,0
Moisture removal volume	L/h	2,7	3,2	4,1	4,9
Sound pressure ⁵⁾	Hi / Med / Lo dB(A)	30/26/23	33/29/25	35/31/27	39/35/29
Sound power	Hi / Med / Lo dB(A)	53/49/46	56/52/48	58/54/50	62/58/52
Dimension	HxWxD mm	250x1000x730	250x1400x730	250x1400x730	250x1400x730
Net weight	kg	30	39	39	39
nanoe X Generator		Mark 2	Mark 2	Mark 2	Mark 2
Outdoor unit		U-71PZH4E8	U-100PZH4E8	U-125PZH4E8	U-140PZH4E8
Power supply	V	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415	380 - 400 - 415
Current	Cool A	3,05 - 2,90 - 2,80	3,85 - 3,70 - 3,50	5,65 - 5,40 - 5,20	6,55 - 6,20 - 6,00
	Heat A	3,15 - 3,00 - 2,90	4,65 - 4,40 - 4,20	6,50 - 6,20 - 5,95	7,75 - 7,40 - 7,05
Air flow	Cool / Heat m ³ /min	62,0/66,0	76,0/70,0	86,0/78,0	89,0/83,0
Sound pressure	Cool / Heat (Hi) dB(A)	48/50	52/52	55/55	56/56
Sound power	Cool / Heat (Hi) dB(A)	65/67	69/69	73/73	74/74
Dimension	HxWxD mm	996x980x370	996x980x370	996x980x370	996x980x370
Net weight	kg	66	82	84	84
Piping diameter	Liquid Inch (mm)	3/8(9,52)	3/8(9,52)	3/8(9,52)	3/8(9,52)
	Gas Inch (mm)	5/8(15,88)	5/8(15,88)	5/8(15,88)	5/8(15,88)
Pipe length range	m	5 - 60	5 - 100	5 - 100	5 - 100
Elevation difference (in / out) ⁸⁾	m	15/30	15/30	15/30	15/30
Pre-charged pipe length	m	30	30	30	30
Additional gas amount	g/m	30	40	40	40
Refrigerant (R32) / CO ₂ Eq.	kg / T	1,95/1,32	2,70/1,82	3,00/2,03	3,00/2,03
Operating range	Cool Min ~ Max °C	-15 ~ +52	-20 ⁹⁾ ~ +52	-20 ⁹⁾ ~ +52	-20 ⁹⁾ ~ +52
	Heat Min ~ Max °C	-20 ~ +24	-20 ~ +24	-20 ~ +24	-20 ~ +24

1) EER and COP calculation is based in accordance to EN14511. 2) For models below 12 kW, the SEER and SCOP is calculated based on values of EU/624/2011. For models above 12 kW, the η_{s,c} / η_{s,h} values is calculated based on EN 14825. 3) Factory setting. 4) Medium external static pressure setting from factory. 5) The sound pressure of the units shows the value measured of the position 1,5 m below the unit. The sound pressure is measured in accordance with Eurovent 6/C/006-97 specification. 6) Connect the liquid socket tube (Ø6,35-Ø9,52) to the liquid tubing side indoor unit. 7) Connect the gas socket tube (Ø12,70-Ø15,88) to the gas tubing side indoor unit. 8) Outdoor unit located lower / outdoor unit located higher. 9) Pipe length up to 30 m. * Recommended fuse for the indoor 3 A. ** Above values are in the case of standard installation(horizontal installation in the ceiling, rear side air intake) and nanoe™ X OFF.

Accessories	
CZ-RTC6W	CONEX wired remote controller (non-wireless), white
CZ-RTC6WBL	CONEX wired remote controller with Bluetooth®, white
CZ-RTC6WBLW	CONEX wired remote controller with Wi-Fi and Bluetooth®, white
CZ-RTC6	CONEX wired remote controller (non-wireless), black
CZ-RTC6BL	CONEX wired remote controller with Bluetooth®, black
CZ-RTC6BLW	CONEX wired remote controller with Wi-Fi and Bluetooth®, black
CZ-RTC5B	Wired remote controller with Econavi function and datanavi
CZ-RWS3 + CZ-RWRC3	Infrared remote controller and receiver
CZ-CAPWFC1	Commercial Wi-Fi Adaptor
PAW-PACR4	Interface to run up to 4 indoor unit groups on backup and alternative run

Accessories	
PAW-WTRAY	Tray for condenser water compatible with outdoor elevation platform
PAW-GRDBSE20	Outdoor base ground support for noise and vibration absorption
PAW-GRDSTD40	Outdoor elevation platform 400x900x400 mm
CZ-CENSC1	Econavi energy saving sensor
CZ-56DAF2	Air outlet plenum for S-3650PF3E
CZ-90DAF2	Air outlet plenum for S-6071PF3E
CZ-160DAF2	Air outlet plenum for S-1014PF3E
PAW-APF800F	NEW BION air pollutant filter for S-3650PF3E
PAW-APF1000F	NEW BION air pollutant filter for S-6071PF3E
PAW-APF1400F	NEW BION air pollutant filter for S-1014PF3E

SEER and SCOP: For S-6071PF3E + U-71PZH4E5. SUPER QUIET: For S-3650PF3E + U-36PZH3E5. INTERNET CONTROL: Optional.

Rating conditions: Cooling indoor 27 °C DB / 19 °C WB, Cooling outdoor 35 °C DB / 24 °C WB, Heating indoor 20 °C DB, Heating outdoor 7 °C DB / 6 °C WB. (DB: Dry Bulb; WB: Wet Bulb). Specifications subject to change without notice. For detailed information about ErP / Energy Labelling, please visit our websites www.aircon.panasonic.eu or www.ptc.panasonic.eu.