


CZ-RD514C
Optional wired
remote controller.

INTERNET CONTROL: Built-in.



NEW Wall Mounted Etherea	Indoor unit Silver	Indoor unit Pure White Matt	Cooling capacity	Heating capacity	Connection in. / out.	Sound pressure ¹⁾		Dimension / Net weight	Piping connections
						Cool — Heat (Hi/Lo/S-Lo)			
						kW	kW		
1,60kW	—	CS-MZ16VKE	1,60	2,60	4 x 1,5	38/26/21	— 39/27/21	295x919x194/9	1/4(6,35)/3/8(9,52)
2,00kW	CS-XZ20VKEW	CS-Z20VKEW	2,00	3,20	4 x 1,5	39/26/21	— 40/27/21	295x919x194/9	1/4(6,35)/3/8(9,52)
2,50kW	CS-XZ25VKEW	CS-Z25VKEW	2,50	3,60	4 x 1,5	41/27/21	— 43/29/21	295x919x194/10	1/4(6,35)/3/8(9,52)
3,50kW	CS-XZ35VKEW	CS-Z35VKEW	3,20	4,50	4 x 1,5	44/30/21	— 45/35/21	295x919x194/10	1/4(6,35)/3/8(9,52)
4,20kW	—	CS-Z42VKEW	4,00	5,60	4 x 1,5	44/33/27	— 45/37/31	295x919x194/10	1/4(6,35)/1/2(12,70)
5,00kW	CS-XZ50VKEW	CS-Z50VKEW	5,00	6,80	4 x 1,5	44/39/32	— 46/39/32	302x1120x236/12	1/4(6,35)/1/2(12,70)
7,10kW	—	CS-Z71VKEW	7,10	8,60	—	49/40/32	— 49/40/32	302x1120x236/13	1/4(6,35)/5/8(15,88)


CZ-RD514C
Optional wired
remote controller.

INTERNET CONTROL: Optional.



Wall Mounted TZ Compact Style	Indoor unit	Cooling capacity	Heating capacity	Connection in. / out.	Sound pressure ¹⁾		Dimension / Net weight	Piping connections
					Cool — Heat (Hi/Lo/S-Lo)			
					kW	kW		
1,60kW	CS-MTZ16TKE	1,60	2,60	4 x 1,5	38/27/22	— 39/28/24	290x799x197/8	1/4(6,35)/3/8(9,52)
2,00kW	CS-TZ20TKEW-1	2,00	3,20	4 x 1,5	39/27/22	— 40/28/24	290x799x197/8	1/4(6,35)/3/8(9,52)
2,50kW	CS-TZ25TKEW-1	2,50	3,60	4 x 1,5	42/28/22	— 42/29/24	290x799x197/8	1/4(6,35)/3/8(9,52)
3,50kW ²⁾	CS-TZ35TKEW-1	3,50	4,50	4 x 1,5	44/32/22	— 44/35/24	290x799x197/8	1/4(6,35)/3/8(9,52)
4,20kW	CS-TZ42TKEW-1	4,20	5,00	4 x 1,5	44/33/31	— 46/37/30	290x799x197/8	1/4(6,35)/1/2(12,70)
5,00kW	CS-TZ50TKEW	5,00	5,30	4 x 1,5	44/39/36	— 46/39/36	302x1102x244/12	1/4(6,35)/1/2(12,70)
6,00kW	CS-TZ60TKEW	6,00	8,50	4 x 1,5	44/39/36	— 47/39/36	302x1102x244/12	1/4(6,35)/1/2(12,70)
7,10kW	CS-TZ71TKEW	7,10	8,70	4 x 1,5	49/40/37	— 49/40/37	302x1102x244/13	1/4(6,35)/1/2(12,70)


CZ-RD514C
Optional wired
remote controller.

INTERNET CONTROL: Optional.



Floor Console ³⁾	Indoor unit	Cooling capacity	Heating capacity	Connection in. / out.	Sound pressure ⁴⁾		Dimension / Net weight	Piping connections
					Cool — Heat (Hi/Lo/S-Lo)			
					kW	kW		
2,00kW	CS-MZ20UFEA	2,00	3,20	4 x 1,5	39/27/22	— 39/27/21	600x750x207/13	1/4(6,35)/3/8(9,52)
2,50kW	CS-Z25UFEAW	2,50	3,60	4 x 1,5	40/27/22	— 40/27/21	600x750x207/13	1/4(6,35)/3/8(9,52)
3,50kW ²⁾	CS-Z35UFEAW	3,50	4,50	4 x 1,5	41/28/22	— 41/28/21	600x750x207/13	1/4(6,35)/3/8(9,52)
5,00kW	CS-Z50UFEAW	5,00	5,30	4 x 1,5	44/33/29	— 48/35/31	600x750x207/13	1/4(6,35)/3/8(9,52)


CZ-BT20EW
RAL9010 panel for 4 Way
60x60 Cassette (sold
separately).

CZ-RD52CP
Optional wired
remote controller.

INTERNET CONTROL READY and EASY CONTROL BY BMS: Optional.



4 Way 60x60 Cassette	Indoor unit (Panel CZ-BT20EW)	Cooling capacity	Heating capacity	Connection in. / out.	Sound pressure ⁶⁾		Dimension / Net weight		Piping connections
					Cool — Heat (Hi/Lo/S-Lo)		Indoor HxWxD	Panel HxWxD	
					kW	kW	mm ²	dB(A)	
2,00kW	CS-MZ20UB4EA	2,00	3,20	4 x 1,5	35/27/24	— 36/30/27	260x575x575/18	51x700x700/2,5	1/4(6,35)/3/8(9,52)
2,50kW	CS-Z25UB4EAW	2,50	3,60	4 x 1,5	36/27/24	— 37/30/27	260x575x575/18	51x700x700/2,5	1/4(6,35)/3/8(9,52)
3,50kW ²⁾	CS-Z35UB4EAW	3,50	4,50	4 x 1,5	36/28/25	— 37/30/27	260x575x575/18	51x700x700/2,5	1/4(6,35)/3/8(9,52)
5,00kW ⁵⁾	CS-Z50UB4EAW	5,00	6,80	4 x 1,5	39/30/27	— 40/31/28	260x575x575/18	51x700x700/2,5	1/4(6,35)/3/8(9,52)
6,00kW	CS-Z60UB4EAW	6,00	8,50	4 x 1,5	44/34/31	— 45/34/31	260x575x575/18	51x700x700/2,5	1/4(6,35)/1/2(12,70)


CZ-RL511D
NEW optional wireless
kit.

INTERNET CONTROL READY and EASY CONTROL BY BMS: Optional.



Low Static Pressure Hide Away	Indoor unit	Cooling capacity	Heating capacity	Connection in. / out.	Sound pressure ⁷⁾		Dimension / Net weight	Piping connections
					Cool — Heat (Hi/Lo/S-Lo)			
					kW	kW		
2,00kW	CS-MZ20UD3EA	2,00	3,20	4 x 1,5	34/29/26	— 36/29/26	200x750x640/19	1/4(6,35)/3/8(9,52)
2,50kW	CS-Z25UD3EAW	2,50	3,60	4 x 1,5	35/29/26	— 37/29/26	200x750x640/19	1/4(6,35)/3/8(9,52)
3,50kW ²⁾	CS-Z35UD3EAW	3,50	4,50	4 x 1,5	35/29/26	— 37/29/26	200x750x640/19	1/4(6,35)/3/8(9,52)
5,00kW ⁵⁾	CS-Z50UD3EAW	5,00	6,80	4 x 1,5	41/31/28	— 41/32/29	200x750x640/19	1/4(6,35)/3/8(9,52)
6,00kW	CS-Z60UD3EAW	6,00	8,50	4 x 1,5	43/32/29	— 43/34/31	200x750x640/19	1/4(6,35)/1/2(12,70)

1) The sound pressure of the indoor unit shows the value measured at a position 1m in front of the main body and 0,8m below the unit. The sound pressure is measured in accordance with JIS C 9612. Q-Lo: Quiet mode. Lo: The lowest set fan speed. 2) The heating capacity is 4,20kW connected to a CU-Z235TBE. 3) Compatible only with 2 ports Outdoor CU-Z235TBE / CU-Z241TBE / CU-Z250TBE. 4) The sound pressure of the units shows the value measured at a position 1m in front of the main body and 1m above floor. The sound pressure is measured in accordance with JIS C 9612. Q-Lo: Quiet mode. Lo: The lowest set fan speed. 5) The heating capacity is 5,30kW connected to a CU-Z250TBE. 6) The sound pressure of the indoor unit shows the value measured at a position 1,5m below the unit. The sound pressure is measured in accordance with JIS C 9612. Q-Lo: Quiet mode. Lo: The lowest set fan speed. 7) The sound pressure of the indoor unit shows the value measured at a position of 1,5m below the unit with 1m duct on the suction side and 2m duct on the discharge side. The sound pressure is measured in accordance with JIS C 9612.