

INVERTER CONSOLE

XPower 42QZA

TURBO

Turbo Mode



Dry Mode



Auto Leak Detection

R32
REFRIGERANT





Ultimate
comfort

INVERTER CONSOLE XPower 42QZA



ELEGANT & COMPACT DESIGN

Carrier console with the elegant & compact design can be used for floor standing or lower wall applications.

As a floor standing model can be semi or fully recessed without loss of capacity. It achieves the set temperature quickly as it supplies air from top and bottom or from top only. Additionally, with the vertical auto swing and the wide-angle louvers, it offers an increased air flow coverage and ensures that warm air reaches the furthest corner of the room.

FEATURES

- | | | | |
|--|--------------------------------|---|---|
|  | 3D Air Flow louvers |  | Sleep Mode |
|  | Fresh air intake |  | Dry Mode |
|  | Built-in Drain Pump (optional) |  | "My" Mode |
|  | Auto Leak Detection |  | Louver Function/ Horizontally |
|  | Auto Defrost |  | Cold Draft Prevention |
|  | Auto Swing |  | Electrical Voltage Protection (168 to 264V) |
|  | Auto Restart |  | Bright LCD Screen Remote Control |
|  | Timer |  | Wired Control |
|  | Turbo Mode | | |

TECHNICAL CHARACTERISTICS

INDOOR UNIT		42QZA012D8S-1	42QZA018D8S-1
OUTDOOR UNIT		38QUS012D8S-1	38QUS018D8S-1
Cooling capacity	kW	3.50 (0.77~3.97)	4.70 (2.64~5.13)
Heating capacity	kW	4.25 (0.46~4.35)	5.00 (2.20~5.24)
Heating capacity at -7°C	kW	2,80	4,40
Heating capacity at -10°C	kW	2,60	3,80
Heating capacity at -15°C	kW	2,40	3,20
SEER/SCOP(average)/SCOP(warmer)	W/W	7.5/4.0/5.5	6.5/4.0/5.0
Energy label		A++ / A+ / A+++	A++ / A+ / A++
Yearly energy consumption	kWh	163/945/865	253/1400/1400
EER/COP	W/W	3.40/3.83	3.01/3.22
Standard current (cooling)	A	4,5	7,0
Standard input (cooling)	W	1030	1560
Standard current (heating)	A	5,0	6,8
Standard input (heating)	W	1110	1550

INDOOR UNIT	42QZA012D8S-1	42QZA018D8S-1	
Sound power level	dB(A)	58	60
Sound pressure level (high/med/low)	dB(A)	41.5/38.0/33.5	45.0/39.0/36.0
Air flow (high/med/low)	m ³ /h	550/465/385	560/480/400
Weight	kg	14.6	14.7
Dimensions (WxDxH)(Body)	mm	700x210x600	700x210x600

OUTDOOR UNIT	38QUS012D8S-1	38QUS018D8S-1	
Temp range cooling	°C	-15~50	
Temp range heating	°C	-15~24	
Liquid side/Gas side		1/4" - 3/8"	1/4" - 1/2"
Standard piping length	m	5	5
Min piping length	m	3	3
Max piping length	m	25	30
Max difference	m	10	20
Additional charge	g/m	12	12
Refrigerant amount	kg	0.72	1.15
Sound power level (high/med/low)	dB(A)	59.40	60.71
Sound pressure level	dB(A)	54	57
Airflow	m ³ /h	2200	2100
Weight	kg	26.6	32.5
Dimensions (WxDxH)	mm	765x303x555	805x330x554
Voltage/Hz/Ph		220~240V / 50Hz / 1Ph	

Notes:
 * Sound data @ cooling mode
 * -7°C / -10°C / -15°C heating @ free frequency

* Preliminary Data

